

Don Latex

Interior acrylic paint



Description:

Don Latex is a water dispersible acrylic white paint. Contain polymers, pigments and additives, finely dispersed in an aqueous phase.

Applications:

Designed for interior painting of walls and ceilings in residential, public and other premises. Don Latex is applied on all mineral surfaces - concrete, masonry and plaster.

Advantages:

- ▲ Good covering
- ▲ Wear resistant
- ▲ Permeable
- ▲ Excellent adhesion to the substrate
- ▲ Easy to maintain and clean
- ▲ Does not contain harmful and dangerous substances for the environment
- ▲ Provides white mat aesthetic surface

Standards:

Don Latex complies with EN 13300:2004.

Method of Use

Surface Preparation:

- ▲ The substrate surface must be undamaged, clean and dry, dustfree and with any contaminants such as grease, mildew, residues of old coatings.
- ▲ In the presence of uneven surfaces fill with product DCP.
- ▲ The base should be primed. It is advisable to use Grundix DP.

Application:

Stir well Don Latex before application.
Dilute with water, if necessary but not more than 5%.

Work at temperatures (of the air and the substrate) in the range between +5°C и +30°C, and relative air humidity below 80%. Don Latex is applied with a brush or paint roller in two coats.

The second layer is after complete drying of the first one (about 3h at ambient temperature of +20 °C).

The recommend is the second layer to be with undiluted paint.

Technical Properties:

Color:	white
Film gloss at 85 °C:	completely mat, < 5
Particle size :	< 100, fine
Wet scrub resistance at 200 cycles:	Class III ≥ 20 < 70
Hiding power:	≥ 98 < 99.5 (Class 2)
Density:	1.42 g/cm ³
Adhesion on substrate:	3.0 N/mm ²
Liquid water permeability:	0.1 - 0.5 II Class
Non-volatile matter content:	56.94 %
Drying:	< 3 h
pH:	7.3
Layer, recommend:	2
Working temperature:	+5 °C to +30 °C

Cleaning:

All tools and equipment should be cleaned immediately after use with clean water.

Coverage:

Depending on substrate: 45 - 65 ml/m²/ coat.

Packaging:

Don Latex is available in packs: 2 l, 5 l, 9 l and 15 l.

Storage:

Don Latex has a shelf life of 12 months if stored in proper conditions, at temperatures range between + 5°C and 35 °C in its original unopened packing.

Don Latex

Keep from freezing!

Cautions

Health and Safety:

Don Latex is not classified as dangerous under proper use.

Avoid contact with skin and eyes.

In case of contact with eyes wash immediately with plenty of water and seek medical advice .

Fire:

Don Latex is water based and is non-flammable.

For further information refer to the Safety Data Sheet.

More from Don Construction Products

A wide range of construction chemicals products are manufactured by DCP which include:

- ▲ Concrete admixtures.
- ▲ Grouts and chemical fixings.
- ▲ Concrete repairs.
- ▲ Industrial floorings.
- ▲ Structural protection.
- ▲ Waterproofing.

Note:

We endeavor to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, due to the fact that we have no direct or continuous control over where or how the products are applied, DCP cannot accept any liability either directly or indirectly arising from the use of DCP products, whether or not in accordance with any advice, specification, recommendation or information given by us.

www.dcp-int.com

 expertise

 quality

 full range