

DECLARATION OF PERFORMANCE

According Annex III of the Regulation (EU) No 305/2011
Amended by Commissions delegated Regulation (EU) No 574/2014
No.: DCDoP - 070011 - 015A



**1. Unique identification code
of the product type:**

Flexseal PU440

2. Intended uses:

Polyurethane sealant for internal and external use in
facade elements and cold climates.

3. Manufacturer:

Don Construction Holdings Ltd
Park House
25-27 Monument Hill
Weybridge
Surrey
KT13 8RT
United Kingdom

4. Authorized representative:

Not Relevant

5. System of AVCP:

System 3

6. Harmonised standard:

EN 15651-1:2012 F-EXT-INT-CC

Notified body:

The notified body **SKZ – TeConA GmbH**, identifica-
tion number **NB 1213**, performed the determina-
tion of the product type on the basis of type testing
under System 3

www.dcp-int.com



DECLARATION OF PERFORMANCE



7. Declared performance:

Pre-Conditioning:

Method B (According to ISO 8340)

Substrate:

Mortar M2 without primer

Aluminium without primer

Essential Characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	See product safety data sheet	
Water tightness and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10 %	
Tensile properties at maintained extension at -30°C	No failure	
Secant tensile modulus at -30°C	Not required	
Tensile properties at maintained extension after immersion in water	No failure	
Durability	Pass	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name:

ILIJAN ILIEV

Place and date of issue:

SOFIA, 10.09.2015

Signature:



www.dcp-int.com



expertise



quality



full range

